

Mackay PVC Hose is constructed using an Ozone and UV resistant Polyvinyl Chloride (PVC) and reinforced for high pressure transfer of Air and Water. Mackay PVC Hose can also be used for short term low pressure transfer of Fuel and Oil.

HOSE SPECIFICATIONS:

- Maximum Recommended Working Pressure for Air and Water: 101psi (0.7MPa)
- Minimum Burst Pressure for Air and Water: 406psi (2.8MPa)
- Working Temperature Range: -10°C to +60°C

APPLICATIONS:

- Transfer of Air.
- Transfer of Water.
- Short term low pressure transfer of Fuel and Oil, such as carbureted lawn mowers.

Caution

- NOT SUITABLE FOR DRINKING WATER.
- NOT SUITABLE FOR LONG TERM CONTACT WITH FUEL OR OIL, OR SUBMERSION IN THESE LIQUIDS AS THE HOSE WILL GO BRITTLE.
- NOT SUITABLE FOR HIGH PRESSURE FUEL APPLICATIONS.
- NOT SUITABLE FOR FUEL TRANSFER IN ENCLOSED SPACES.
- NOT SUITABLE FOR MARINE FUEL APPLICATIONS.



8mm	5/16"	PVC8X20	20m	Small Box
10mm	3/8"	PVC10X20	20m	Small Box
13mm	1/2"	PVC13X20	20m	Large Box
16mm	5/8"	PVC16X10	10m	Large Box
19mm	3/4"	PVC19X10	10m	Large Box